



PAPER CELLULOSE OIL TEC/SEAL 770

It is cellulose fiber gasket material suitable for any type of sealing applications such as material handling equipments, chemical pumps and pipe line diesel engines oil fuel water pumps carburetor gear box oil pans etc binders used are nitrile and butadiene rubber.

PROPIEDADES

Operating Temperature	150°C
Density	ASTM F1315 0.85-0.05g/cm ²
Compressibility % AT Kg/cm ² (1000PSI)	ASTM F36 15-25%
Recovery	ASTM F36 35%
Tensile Strength Kg/cm ²	ASTM F152 140
Fluid Resistance - ASTM OIL N°3	ASTM 146
Thickness Increase	10%
Weight Increase	40%
ASTM FUEL B	ASTM F146
Thickness Increase	10%
Weight Increase	40%
In Water	AST F146
Thickness Increase	35%
Weight Increase	65%



📍 Sucursal Bogotá - Colombia

Carrera 69B No. 34-02 Sur
Barrio Carvajal

☎ 60(1) 443 1050 - 3913645
📞 314 790 8267 / 311 807 1433

📍 Sucursal Dosquebradas - Colombia

Bodega 54 zona industrial
antigua plaza de las ferias

☎ 60(6) 349 7350
📞 316 874 3507

